



GEFORCE 9800 GTX OC2™

PCI EXPRESS x16

512MB GDDR3 MEMORY CHANNEL

RETAIL Part Number: **BFGR98512GTXOC2E** UPC: **876758002210**
CHANNEL Part Number: **BFGE98512GTXOC2E** UPC: **876758002227**

The **BFG NVIDIA® GeForce® 9800 GTX OC2™ 512MB** graphics card raises the performance bar by enabling full-throttle lifelike game play at **intense resolutions** and is **OC2™ overlocked** to deliver **improved frame rates** and **better overall performance** in the hottest Microsoft® DirectX® 10 games. The PureVideo® HD engine delivers **unmatched video and movie quality** with **spectacular picture clarity** featuring scene-optimized color and contrast enhancement. And when coupled with nForce® SLI®-ready motherboards, provides **amplified performance** up to 2x in a dual SLI configuration and up to 2.8x in 3-way SLI mode.

Specifications

- GPU: NVIDIA GeForce 9800 GTX
- Bus Type: PCI Express® 2.0
- Memory: 512MB GDDR3
- Overclocked Core Clock: 715MHz (vs. 675MHz standard)
- Overclocked Shader Clock: 1782MHz (vs. 1688MHz standard)
- Memory Data Rate: 2250MHz (vs. 2200MHz standard)
- Stream Processors: 128
- Shader Model: 4.0
- Texture Fill Rate: 45.8 Billion/sec.
- Memory Interface: 256-bit
- Memory Bandwidth: 72.0GB/sec.
- API Support: Microsoft® DirectX® 10 and lower, OpenGL® 2.1 and lower for Microsoft Windows®
- Display Connectors: 2 Dual-Link DVI-I, HDTV + TV Out
- RAMDACs: Dual 400MHz
- HDCP Capable: Yes, Dual Link*
- HDMI™ Capable: Yes

Included in Box

- BFG NVIDIA GeForce 9800 GTX OC2™ 512MB Graphics Card
- Quick install guide
- DVI to VGA adapter
- DVI to HDMI adapter
- S/PDIF audio cable
- Dual 4-pin Molex® to single 6-pin PCI Express power adapter
- HDTV (component) breakout cable
- Driver CD, which includes
 - > NVIDIA Forceware® unified graphics driver
 - > Full multiple language installation manual .pdf



Minimum System Requirements

- 1GB of system memory
- CD or DVD-ROM drive
- 100MB of available hard disk drive space for basic driver installation
- Microsoft Windows Vista™ or XP operating system
- PCI Express or PCI Express 2.0-compliant system motherboard with one vacant PCI Express x16 slot
- One vacant add-in card slot below the PCI Express x16 slot. This graphics card physically occupies two slots
- 475W PCI Express-compliant system power supply with a combined 12V current rating of 26A or more**
- Two 6-pin PCI Express supplementary power connectors -or- One 6-pin PCI Express and two 4-pin Molex supplementary power connectors

NOTE: For the power requirements of two or more GeForce 9800 GTX-based graphics cards in an NVIDIA SLI configuration, please visit www.bfgtech.com/slipower.

* Requires other compatible components that are HDCP capable. Designed to meet the output protection management (HDCP) and security specifications of the HD DVD and Blu-ray Disc® formats, allowing the playback of encrypted movie content on PCs when connected to HDCP-compliant displays.

** Minimum system power requirement based on a PC configured with an Intel Core®2 Duo E4500 processor.

† Toll-free telephone technical support is available in the United States and Canada only. For customers outside of North America, a toll call will apply and your phone bill will reflect the charge. E-mail tech support is free and available to all customers.

© 2008, BFG Technologies, OC, BFG Tech and the BFG Technologies logo are trademarks or registered trademarks of BFG Technologies, Inc. All rights reserved. All other trademarks are the property of their respective owners. BFG Tech reserves the right to change product specifications and box contents without notice. Product Made in China.

Optional Monitor Size

	17"-19"	20"-22"	23"-28"	30"+
Gaming and 3D Applications	✓	✓	✓	✓
Vista Aero and 2D Applications	✓	✓	✓	✓

For more information on monitor resolutions visit www.bfgtech.com.



LIFETIME WARRANTY 24/7/365 TECH SUPPORT†

28690 Ballard Drive | Lake Forest, Illinois 60045 | 847.281.3110 | sales@bfgtech.com | support@bfgfix.com | www.bfgtech.com

[BFG Tech]