



GEFORCE® 9800 GT OC2™

PCI EXPRESS® x16

Thermo Intelligence®
custom cooling solution

512MB GDDR3 MEMORY

CHANNEL Part Number: **BFG98512GTOC2FE** UPC: **876758002517**

A new and improved true 9800 GT by BFG—providing an amazing overclock with a 55nm GPU and minimum heat! The **BFG GeForce® 9800 GT OC2™** graphics card with **ThermoIntelligence®** is factory overclocked and the GPU operates **up to 30°C cooler!** BFG's ThermoIntelligence Custom Cooling Solution offers amazing thermal performance in a quiet dual-slot design. This cooling solution also features green LED lights to add visual flair to your rig.



Specifications

- **GPU:** NVIDIA® GeForce® 9800 GT
- **Bus Type:** PCI Express® 2.0
- **Memory:** 512MB GDDR3
- **Core Clock:** 650MHz (vs. 600MHz standard)
- **Shader Clock:** 1620MHz (vs. 1500MHz standard)
- **Memory Data Rate:** 1926MHz (vs. 1800MHz standard)
- **Stream Processors:** 112
- **Shader Model:** 4.0
- **Texture Fill Rate:** 36.4 Billion/sec.
- **Memory Interface:** 256-bit
- **Memory Bandwidth:** 61.6GB/sec.
- **API Support:** Microsoft® DirectX® 10 and lower, OpenGL® 2.1 and lower for Microsoft Windows®
- **Display Connectors:** 2 Dual-Link DVI-I, HDTV + TV Out
- **RAMDACs:** Dual 400MHz
- **HDCP Capable:** Yes, Dual-Link**
- **HDMI™ Capable:** Yes***
- **NVIDIA® SLI® Support:** Yes, 2-Way

Included in Box

- BFG NVIDIA® 9800 GT OC2™ 512MB graphics card with ThermoIntelligence® Custom Cooling Solution
- Quick install guide
- DVI to VGA adapter
- HDTV (component) breakout cable
- Dual 4-pin peripheral to single 6-pin PCI Express® power adapter
- **Driver CD, which includes**
 - > NVIDIA® Forceware® unified graphics driver
 - > Full multiple language installation manual .pdf

Minimum System Requirements

- 1GB of system memory
- CD or DVD-ROM drive
- 100MB of available hard disk drive space for basic driver installation
- Microsoft® Windows Vista™ or XP operating system
- PCI Express® or PCI Express® 2.0-compliant system motherboard with one vacant PCI Express® x16 slot
- One vacant add-in card slot below the PCI Express® x16 slot. This graphics card physically occupies two slots
- 425W PCI Express®-compliant system power supply with a combined 12V current rating of 28A or more****
- One 6-pin PCI Express® supplementary power connector -or- Two 4-pin peripheral supplementary power connectors

NOTE: For the power requirements of multiple GeForce® 9800 GT-based graphics cards in an NVIDIA SLI® configuration, please visit www.bfgtech.com/slipower.

* **Product must be registered on www.bfgtech.com within thirty (30) calendar days of the original purchase date to activate the limited lifetime warranty or limited ten (10) year warranty. Upon registration the product is protected for the product's lifetime in the United States and Canada, and ten (10) years from the date of purchase in all countries outside of North America against defects in material and workmanship. Warranty coverage is subject to the provisions available at www.bfgtech.com. Products not properly registered will be covered from the date of purchase by a two (2) year limited warranty in Europe and a one (1) year limited warranty in the United States and other countries. Proper registration includes submitting proof of purchase to BFG.**

** Requires other compatible components that are HDCP capable. Designed to meet the output protection management (HDCP) and security specifications of the HD DVD and Blu-ray Disc® formats, allowing the playback of encrypted movie content on PCs when connected to HDCP-compliant displays.

*** Requires adapter and audio cable (sold separately).

**** Minimum system power requirement based on a standard PC configured with an Intel Core® 2 Extreme X6800 processor.

† Toll-free telephone technical support is available in the United States and Canada only. For customers outside of North America, a toll call will apply and your phone bill will reflect the charge. E-mail tech support is free and available to all customers.

© 2008, BFG Technologies. BFG Tech and the BFG Technologies logo are trademarks or registered trademarks of BFG Technologies, Inc. All rights reserved. All other trademarks are the property of their respective owners. BFG Tech reserves the right to change product specifications and box contents without notice. Product Made in China.

Optimal Monitor Size

	17"-19"	20"-22"	23"-28"	30"
Gaming and 3D Applications	✓	✓	✓	
Vista Aero and 2D Applications	✓	✓	✓	✓

For more information on monitor resolutions visit www.bfgtech.com



LIFETIME WARRANTY* 24/7/365 TECH SUPPORT†

28690 Ballard Drive | Lake Forest, Illinois 60045 | 847.281.3110 | sales@bfgtech.com | support@bfgfix.com | www.bfgtech.com

[BFG Tech]